

## 54AC/74AC163 • 54ACT/74ACT163 Synchronous Presettable Binary Counter

### General Description



The 'AC/'ACT163 are high-speed synchronous modulo-16 binary counters. They are synchronously presettable for application in programmable dividers and have two types of Count Enable inputs plus a Terminal Count output for versatility in forming synchronous multistage counters. The 'AC/'ACT163 has a Synchronous Reset input that overrides counting and parallel loading and allows the outputs to be simultaneously reset on the rising edge of the clock.

### Features

- Synchronous counting and loading
- High-speed synchronous expansion
- Typical count rate of 125 MHz
- Outputs source/sink 24 mA
- 'ACT163 has TTL-compatible inputs
- Standard Military Drawing (SMD)
  - 'AC163: 5962-89582


**Ordering Code:** See Section 8

### Logic Symbols




### Connection Diagrams

**Pin Assignment  
for DIP, Flatpak and SOIC**



**Pin Assignment  
for LCC**



| Pin Names                      | Description                 |
|--------------------------------|-----------------------------|
| CEP                            | Count Enable Parallel Input |
| CET                            | Count Enable Trickle Input  |
| CP                             | Clock Pulse Input           |
| SR                             | Synchronous Reset Input     |
| P <sub>0</sub> -P <sub>3</sub> | Parallel Data Inputs        |
| PE                             | Parallel Enable Input       |
| Q <sub>0</sub> -Q <sub>3</sub> | Flip-Flop Outputs           |
| TC                             | Terminal Count Output       |

## Functional Description

The 'AC/ACT163 counts in modulo-16 binary sequence. From state 15 (HHHH) it increments to state 0 (LLLL). The clock inputs of all flip-flops are driven in parallel through a clock buffer. Thus all changes of the Q outputs occur as a result of, and synchronous with, the LOW-to-HIGH transition of the CP input signal. The circuits have four fundamental modes of operation, in order of precedence: synchronous reset, parallel load, count-up and hold. Four control inputs—Synchronous Reset ( $\overline{SR}$ ), Parallel Enable ( $\overline{PE}$ ), Count Enable Parallel (CEP) and Count Enable Trickle (CET)—determine the mode of operation, as shown in the Mode Select Table. A LOW signal on  $\overline{SR}$  overrides counting and parallel loading and allows all outputs to go LOW on the next rising edge of CP. A LOW signal on  $\overline{PE}$  overrides counting and allows information on the Parallel Data ( $P_n$ ) inputs to be loaded into the flip-flops on the next rising edge of CP. With  $\overline{PE}$  and  $\overline{SR}$  HIGH, CEP and CET permit counting when both are HIGH. Conversely, a LOW signal on either CEP or CET inhibits counting.

The 'AC/ACT163 uses D-type edge-triggered flip-flops and changing the  $\overline{SR}$ ,  $\overline{PE}$ , CEP and CET inputs when the CP is in either state does not cause errors, provided that the recommended setup and hold times, with respect to the rising edge of CP, are observed.

The Terminal Count (TC) output is HIGH when CET is HIGH and counter is in state 15. To implement synchronous multi-stage counters, the TC outputs can be used with the CEP and CET inputs in two different ways.

Figure 1 shows the connections for simple ripple carry, in which the clock period must be longer than the CP to TC delay of the first stage, plus the cumulative CET to TC delays of the intermediate stages, plus the CET to CP setup time of the last stage. This total delay plus setup time sets the upper limit on clock frequency. For faster clock rates, the carry lookahead connections shown in Figure 2 are recommended. In this scheme the ripple delay through the intermediate stages commences with the same clock that causes the first stage to tick over from max to min in the Up mode, or min to max in the Down mode, to start its final cycle. Since this final cycle takes 16 clocks to complete, there is plenty of time for the ripple to progress through the intermediate stages. The critical timing that limits the clock period is the CP to TC delay of the first stage plus the CEP to CP setup time of the last stage. The TC output is subject

to decoding spikes due to internal race conditions and is therefore not recommended for use as a clock or asynchronous reset for flip-flops, registers or counters. For such applications, the Clocked Carry (CC) output is provided. The CC output is normally HIGH. When  $\overline{CEP}$ ,  $\overline{CET}$ , and  $\overline{TC}$  are LOW, the CC output will go LOW when the clock next goes LOW and will stay LOW until the clock goes HIGH again, as shown in the CC Truth Table. When the Output Enable ( $\overline{OE}$ ) is LOW, the parallel data outputs  $Q_0$ – $Q_3$  are active and follow the flip-flop Q outputs. A HIGH signal on  $\overline{OE}$  forces  $Q_0$ – $Q_3$  to the High Z state but does not prevent counting, loading or resetting.

$$\text{Logic Equations: Count Enable} = \text{CEP} \cdot \text{CET} \cdot \overline{\text{PE}}$$


$$\text{TC} = Q_0 \cdot Q_1 \cdot Q_2 \cdot Q_3 \cdot \text{CET}$$

Mode Select Table

| $\overline{SR}$ | $\overline{PE}$ | CET | CEP | Action on the Rising Clock Edge ( $\nearrow$ ) |
|-----------------|-----------------|-----|-----|------------------------------------------------|
| L               | X               | X   | X   | Reset (Clear)                                  |
| H               | L               | X   | X   | Load ( $P_n \rightarrow Q_n$ )                 |
| H               | H               | H   | H   | Count (Increment)                              |
| H               | H               | L   | X   | No Change (Hold)                               |
| H               | H               | X   | L   | No Change (Hold)                               |

H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial

## State Diagram



TL/F/9932-5




FIGURE 1

TL/F/9932-8





FIGURE 2

TL/F/9932-9

# Block Diagram



TL/F/9932-6

Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

## Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

|                                                                        |                          |
|------------------------------------------------------------------------|--------------------------|
| Supply Voltage ( $V_{CC}$ )                                            | -0.5V to +7.0V           |
| DC Input Diode Current ( $I_{IK}$ )                                    |                          |
| $V_I = -0.5V$                                                          | -20 mA                   |
| $V_I = V_{CC} + 0.5V$                                                  | +20 mA                   |
| DC Input Voltage ( $V_I$ )                                             | -0.5V to $V_{CC} + 0.5V$ |
| DC Output Diode Current ( $I_{OK}$ )                                   |                          |
| $V_O = -0.5V$                                                          | -20 mA                   |
| $V_O = V_{CC} + 0.5V$                                                  | +20 mA                   |
| DC Output Voltage ( $V_O$ )                                            | -0.5V to $V_{CC} + 0.5V$ |
| DC Output Source or Sink Current ( $I_O$ )                             | ±50 mA                   |
| DC $V_{CC}$ or Ground Current per Output Pin ( $I_{CC}$ or $I_{GND}$ ) | ±50 mA                   |
| Storage Temperature ( $T_{STG}$ )                                      | -65°C to +150°C          |
| Junction Temperature ( $T_J$ )                                         |                          |
| CDIP                                                                   | 175°C                    |
| PDIP                                                                   | 140°C                    |

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT™ circuits outside databook specifications.

## Recommended Operating Conditions

|                                                 |                 |
|-------------------------------------------------|-----------------|
| Supply Voltage ( $V_{CC}$ )                     |                 |
| 'AC                                             | 2.0V to 6.0V    |
| 'ACT                                            | 4.5V to 5.5V    |
| Input Voltage ( $V_I$ )                         | 0V to $V_{CC}$  |
| Output Voltage ( $V_O$ )                        | 0V to $V_{CC}$  |
| Operating Temperature ( $T_A$ )                 |                 |
| 74AC/ACT                                        | -40°C to +85°C  |
| 54AC/ACT                                        | -55°C to +125°C |
| Minimum Input Edge Rate ( $\Delta V/\Delta t$ ) |                 |
| 'AC Devices                                     |                 |
| $V_{IN}$ from 30% to 70% of $V_{CC}$            |                 |
| $V_{CC}$ @ 3.3V, 4.5V, 5.5V                     | 125 mV/ns       |
| Minimum Input Edge Rate ( $\Delta V/\Delta t$ ) |                 |
| 'ACT Devices                                    |                 |
| $V_{IN}$ from 0.8V to 2.0V                      |                 |
| $V_{CC}$ @ 4.5V, 5.5V                           | 125 mV/ns       |

## DC Characteristics for 'AC Family Devices

| Symbol          | Parameter                         | V <sub>CC</sub><br>(V) | 74AC                   |                   | 54AC                                | 74AC                               | Units | Conditions                                                                                          |
|-----------------|-----------------------------------|------------------------|------------------------|-------------------|-------------------------------------|------------------------------------|-------|-----------------------------------------------------------------------------------------------------|
|                 |                                   |                        | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> =<br>−55°C to +125°C | T <sub>A</sub> =<br>−40°C to +85°C |       |                                                                                                     |
|                 |                                   |                        | Typ                    | Guaranteed Limits |                                     |                                    |       |                                                                                                     |
| V <sub>IH</sub> | Minimum High Level Input Voltage  | 3.0                    | 1.5                    | 2.1               | 2.1                                 | 2.1                                | V     | V <sub>OUT</sub> = 0.1V<br>or V <sub>CC</sub> − 0.1V                                                |
|                 |                                   | 4.5                    | 2.25                   | 3.15              | 3.15                                | 3.15                               |       |                                                                                                     |
|                 |                                   | 5.5                    | 2.75                   | 3.85              | 3.85                                | 3.85                               |       |                                                                                                     |
| V <sub>IL</sub> | Maximum Low Level Input Voltage   | 3.0                    | 1.5                    | 0.9               | 0.9                                 | 0.9                                | V     | V <sub>OUT</sub> = 0.1V<br>or V <sub>CC</sub> − 0.1V                                                |
|                 |                                   | 4.5                    | 2.25                   | 1.35              | 1.35                                | 1.35                               |       |                                                                                                     |
|                 |                                   | 5.5                    | 2.75                   | 1.65              | 1.65                                | 1.65                               |       |                                                                                                     |
| V <sub>OH</sub> | Minimum High Level Output Voltage | 3.0                    | 2.99                   | 2.9               | 2.9                                 | 2.9                                | V     | I <sub>OUT</sub> = −50 μA                                                                           |
|                 |                                   | 4.5                    | 4.49                   | 4.4               | 4.4                                 | 4.4                                |       |                                                                                                     |
|                 |                                   | 5.5                    | 5.49                   | 5.4               | 5.4                                 | 5.4                                |       |                                                                                                     |
|                 |                                   | 3.0                    |                        | 2.56              | 2.4                                 | 2.46                               | V     | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>−12 mA<br>I <sub>OH</sub> −24 mA<br>−24 mA |
|                 |                                   | 4.5                    |                        | 3.86              | 3.7                                 | 3.76                               |       |                                                                                                     |
|                 |                                   | 5.5                    |                        | 4.86              | 4.7                                 | 4.76                               |       |                                                                                                     |
| V <sub>OL</sub> | Maximum Low Level Output Voltage  | 3.0                    | 0.002                  | 0.1               | 0.1                                 | 0.1                                | V     | I <sub>OUT</sub> = 50 μA                                                                            |
|                 |                                   | 4.5                    | 0.001                  | 0.1               | 0.1                                 | 0.1                                |       |                                                                                                     |
|                 |                                   | 5.5                    | 0.001                  | 0.1               | 0.1                                 | 0.1                                |       |                                                                                                     |
|                 |                                   | 3.0                    |                        | 0.36              | 0.50                                | 0.44                               | V     | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>12 mA<br>I <sub>OL</sub> 24 mA<br>24 mA    |
|                 |                                   | 4.5                    |                        | 0.36              | 0.50                                | 0.44                               |       |                                                                                                     |
|                 |                                   | 5.5                    |                        | 0.36              | 0.50                                | 0.44                               |       |                                                                                                     |
| I <sub>IN</sub> | Maximum Input Leakage Current     | 5.5                    |                        | ±0.1              | ±1.0                                | ±1.0                               | μA    | V <sub>I</sub> = V <sub>CC</sub> , GND                                                              |

\*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

## DC Characteristics for 'AC Family Devices (Continued)

| Symbol           | Parameter                           | V <sub>CC</sub><br>(V) | 74AC                   |                   | 54AC                                |  | 74AC                               |  | Units | Conditions                                  |
|------------------|-------------------------------------|------------------------|------------------------|-------------------|-------------------------------------|--|------------------------------------|--|-------|---------------------------------------------|
|                  |                                     |                        | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> =<br>–55°C to +125°C |  | T <sub>A</sub> =<br>–40°C to +85°C |  |       |                                             |
|                  |                                     |                        | Typ                    | Guaranteed Limits |                                     |  |                                    |  |       |                                             |
| I <sub>OLD</sub> | †Minimum Dynamic<br>Output Current  | 5.5                    |                        |                   | 50                                  |  | 75                                 |  | mA    | V <sub>OLD</sub> = 1.65V Max                |
| I <sub>OHD</sub> |                                     | 5.5                    |                        |                   | –50                                 |  | –75                                |  | mA    | V <sub>OHD</sub> = 3.85V Min                |
| I <sub>CC</sub>  | Maximum Quiescent<br>Supply Current | 5.5                    |                        | 8.0               | 160.0                               |  | 80.0                               |  | μA    | V <sub>IN</sub> = V <sub>CC</sub><br>or GND |

\*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

Note: I<sub>IN</sub> and I<sub>CC</sub> @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V V<sub>CC</sub>.

I<sub>CC</sub> for 54AC @ 25°C is identical to 74AC @ 25°C.

## DC Characteristics for 'ACT Family Devices

| Symbol           | Parameter                         | V <sub>CC</sub><br>(V) | 74ACT                  |                   | 54ACT                               |  | 74ACT                              |  | Units | Conditions                                                                                |
|------------------|-----------------------------------|------------------------|------------------------|-------------------|-------------------------------------|--|------------------------------------|--|-------|-------------------------------------------------------------------------------------------|
|                  |                                   |                        | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> =<br>–55°C to +125°C |  | T <sub>A</sub> =<br>–40°C to +85°C |  |       |                                                                                           |
|                  |                                   |                        | Typ                    | Guaranteed Limits |                                     |  |                                    |  |       |                                                                                           |
| V <sub>IH</sub>  | Minimum High Level Input Voltage  | 4.5                    | 1.5                    | 2.0               | 2.0                                 |  | 2.0                                |  | V     | V <sub>OUT</sub> = 0.1V<br>or V <sub>CC</sub> – 0.1V                                      |
|                  |                                   | 5.5                    | 1.5                    | 2.0               | 2.0                                 |  | 2.0                                |  |       |                                                                                           |
| V <sub>IL</sub>  | Maximum Low Level Input Voltage   | 4.5                    | 1.5                    | 0.8               | 0.8                                 |  | 0.8                                |  | V     | V <sub>OUT</sub> = 0.1V<br>or V <sub>CC</sub> – 0.1V                                      |
|                  |                                   | 5.5                    | 1.5                    | 0.8               | 0.8                                 |  | 0.8                                |  |       |                                                                                           |
| V <sub>OH</sub>  | Minimum High Level Output Voltage | 4.5                    | 4.49                   | 4.4               | 4.4                                 |  | 4.4                                |  | V     | I <sub>OUT</sub> = –50 μA                                                                 |
|                  |                                   | 5.5                    | 5.49                   | 5.4               | 5.4                                 |  | 5.4                                |  |       |                                                                                           |
|                  |                                   | 4.5                    |                        | 3.86              | 3.70                                |  | 3.76                               |  | V     | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>–24 mA<br>I <sub>OH</sub> –24 mA |
|                  |                                   | 5.5                    |                        | 4.86              | 4.70                                |  | 4.76                               |  |       |                                                                                           |
| V <sub>OL</sub>  | Maximum Low Level Output Voltage  | 4.5                    | 0.001                  | 0.1               | 0.1                                 |  | 0.1                                |  | V     | I <sub>OUT</sub> = 50 μA                                                                  |
|                  |                                   | 5.5                    | 0.001                  | 0.1               | 0.1                                 |  | 0.1                                |  |       |                                                                                           |
|                  |                                   | 4.5                    |                        | 0.36              | 0.50                                |  | 0.44                               |  | V     | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>24 mA<br>I <sub>OL</sub> 24 mA   |
|                  |                                   | 5.5                    |                        | 0.36              | 0.50                                |  | 0.44                               |  |       |                                                                                           |
| I <sub>IN</sub>  | Maximum Input Leakage Current     | 5.5                    |                        | ±0.1              | ±1.0                                |  | ±1.0                               |  | μA    | V <sub>I</sub> = V <sub>CC</sub> , GND                                                    |
| I <sub>CCT</sub> | Maximum I <sub>CC</sub> /Input    | 5.5                    | 0.6                    |                   | 1.6                                 |  | 1.5                                |  | mA    | V <sub>I</sub> = V <sub>CC</sub> – 2.1V                                                   |
| I <sub>OLD</sub> | †Minimum Dynamic Output Current   | 5.5                    |                        |                   | 50                                  |  | 75                                 |  | mA    | V <sub>OLD</sub> = 1.65V Max                                                              |
| I <sub>OHD</sub> |                                   | 5.5                    |                        |                   | –50                                 |  | –75                                |  | mA    | V <sub>OHD</sub> = 3.85V Min                                                              |
| I <sub>CC</sub>  | Maximum Quiescent Supply Current  | 5.5                    |                        | 8.0               | 160.0                               |  | 80.0                               |  | μA    | V <sub>IN</sub> = V <sub>CC</sub><br>or GND                                               |

\*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

Note: I<sub>CC</sub> for 54ACT @ 25°C is identical to 74ACT @ 25°C.

# **AC Electrical Characteristics:** See Section 2 for waveforms

| Symbol           | Parameter                                                         | V <sub>CC</sub> *<br>(V) | 74AC                                             |             |              | 54AC                                                          |              | 74AC                                                         |              | Units | Fig. No. |
|------------------|-------------------------------------------------------------------|--------------------------|--------------------------------------------------|-------------|--------------|---------------------------------------------------------------|--------------|--------------------------------------------------------------|--------------|-------|----------|
|                  |                                                                   |                          | T <sub>A</sub> = +25°C<br>C <sub>L</sub> = 50 pF |             |              | T <sub>A</sub> = -55°C<br>to +125°C<br>C <sub>L</sub> = 50 pF |              | T <sub>A</sub> = -40°C<br>to +85°C<br>C <sub>L</sub> = 50 pF |              |       |          |
|                  |                                                                   |                          | Min                                              | Typ         | Max          | Min                                                           | Max          | Min                                                          | Max          |       |          |
| f <sub>max</sub> | Maximum Clock Frequency                                           | 3.3<br>5.0               | 70<br>110                                        | 95<br>140   |              | 55<br>90                                                      |              | 60<br>95                                                     |              | MHz   |          |
| t <sub>PLH</sub> | Propagation Delay, CP to Q <sub>n</sub><br>(PE Input HIGH or LOW) | 3.3<br>5.0               | 2.0<br>1.5                                       | 7.5<br>5.5  | 12.5<br>9.0  | 1.0<br>1.0                                                    | 13.5<br>9.5  | 1.5<br>1.0                                                   | 13.5<br>9.5  | ns    | 2-3,4    |
| t <sub>PHL</sub> | Propagation Delay, CP to Q <sub>n</sub><br>(PE Input HIGH or LOW) | 3.3<br>5.0               | 1.5<br>1.5                                       | 8.5<br>6.0  | 12.0<br>9.5  | 1.0<br>1.0                                                    | 12.5<br>9.5  | 1.5<br>1.5                                                   | 13.0<br>10.0 | ns    | 2-3,4    |
| t <sub>PLH</sub> | Propagation Delay<br>CP to TC                                     | 3.3<br>5.0               | 3.0<br>2.0                                       | 9.5<br>7.0  | 15.0<br>10.5 | 1.0<br>1.0                                                    | 16.5<br>11.0 | 2.5<br>1.5                                                   | 16.5<br>11.5 | ns    | 2-3,4    |
| t <sub>PHL</sub> | Propagation Delay<br>CP to TC                                     | 3.3<br>5.0               | 3.5<br>2.0                                       | 11.0<br>8.0 | 14.0<br>11.0 | 1.0<br>1.0                                                    | 15.0<br>11.0 | 2.5<br>2.0                                                   | 15.5<br>11.5 | ns    | 2-3,4    |
| t <sub>PLH</sub> | Propagation Delay<br>CET to TC                                    | 3.3<br>5.0               | 2.0<br>1.5                                       | 7.5<br>5.5  | 9.5<br>6.5   | 1.0<br>1.0                                                    | 11.0<br>7.5  | 1.5<br>1.0                                                   | 11.0<br>7.5  | ns    | 2-3,4    |
| t <sub>PHL</sub> | Propagation Delay<br>CET to TC                                    | 3.3<br>5.0               | 2.5<br>2.0                                       | 8.5<br>6.0  | 11.0<br>8.5  | 1.0<br>1.0                                                    | 12.0<br>9.0  | 2.0<br>1.5                                                   | 12.5<br>9.5  | ns    | 2-3,4    |

\*Voltage Range 3.3 is 3.3V ± 0.3V  
Voltage Range 5.0 is 5.0V ± 0.5V

## **AC Operating Requirements:** See Section 2 for waveforms

| Symbol         | Parameter                                       | V <sub>CC</sub> *<br>(V) | 74AC                                             |                    | 54AC                                                          | 74AC                                                         | Units | Fig. No. |
|----------------|-------------------------------------------------|--------------------------|--------------------------------------------------|--------------------|---------------------------------------------------------------|--------------------------------------------------------------|-------|----------|
|                |                                                 |                          | T <sub>A</sub> = +25°C<br>C <sub>L</sub> = 50 pF |                    | T <sub>A</sub> = -55°C<br>to +125°C<br>C <sub>L</sub> = 50 pF | T <sub>A</sub> = -40°C<br>to +85°C<br>C <sub>L</sub> = 50 pF |       |          |
|                |                                                 |                          | Typ                                              | Guaranteed Minimum |                                                               |                                                              |       |          |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>P <sub>n</sub> to CP | 3.3<br>5.0               | 5.5<br>4.0                                       | 13.5<br>8.5        | 17.0<br>11.0                                                  | 16.0<br>10.5                                                 | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>P <sub>n</sub> to CP  | 3.3<br>5.0               | -7.0<br>-5.0                                     | -1.0<br>0          | -0.5<br>0                                                     | -0.5<br>0                                                    | ns    | 2-7      |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>SR to CP             | 3.3<br>5.0               | 5.5<br>4.0                                       | 14.0<br>9.5        | 17.0<br>12.0                                                  | 16.5<br>11.0                                                 | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>SR to CP              | 3.3<br>5.0               | -7.5<br>-5.5                                     | -1.0<br>-0.5       | -0.5<br>0                                                     | -0.5<br>0                                                    | ns    | 2-7      |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>PE to CP             | 3.3<br>5.0               | 5.5<br>4.0                                       | 11.5<br>7.5        | 16.0<br>9.5                                                   | 14.0<br>8.5                                                  | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>PE to CP              | 3.3<br>5.0               | -7.5<br>-5.0                                     | -1.0<br>-0.5       | -0.5<br>0                                                     | -0.5<br>0                                                    | ns    | 2-7      |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>CEP or CET to CP     | 3.3<br>5.0               | 3.5<br>2.5                                       | 6.0<br>4.5         | 8.0<br>5.5                                                    | 7.0<br>5.0                                                   | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>CEP or CET to CP      | 3.3<br>5.0               | -4.5<br>-3.0                                     | 0<br>0             | 0<br>0.5                                                      | 0<br>0.5                                                     | ns    | 2-7      |
| t <sub>w</sub> | Clock Pulse Width (Load)<br>HIGH or LOW         | 3.3<br>5.0               | 3.0<br>2.0                                       | 3.5<br>2.5         | 5.0<br>5.0                                                    | 4.0<br>3.0                                                   | ns    | 2-3      |
| t <sub>w</sub> | Clock Pulse Width (Count)<br>HIGH or LOW        | 3.3<br>5.0               | 3.0<br>2.0                                       | 4.0<br>3.0         | 5.0<br>5.0                                                    | 4.5<br>3.5                                                   | ns    | 2-3      |

\*Voltage Range 3.3 is 3.3V ± 0.3V  
Voltage Range 5.0 is 5.0V ± 0.5V

## AC Electrical Characteristics: See Section 2 for waveforms

| Symbol           | Parameter                                                         | V <sub>CC</sub> *<br>(V) | 74ACT                                             |     |      | 54ACT                                                          |     | 74ACT                                                          |      | Units | Fig. No. |
|------------------|-------------------------------------------------------------------|--------------------------|---------------------------------------------------|-----|------|----------------------------------------------------------------|-----|----------------------------------------------------------------|------|-------|----------|
|                  |                                                                   |                          | T <sub>A</sub> = + 25°C<br>C <sub>L</sub> = 50 pF |     |      | T <sub>A</sub> = –55°C<br>to + 125°C<br>C <sub>L</sub> = 50 pF |     | T <sub>A</sub> = – 40°C<br>to + 85°C<br>C <sub>L</sub> = 50 pF |      |       |          |
|                  |                                                                   |                          | Min                                               | Typ | Max  | Min                                                            | Max | Min                                                            | Max  |       |          |
| t <sub>max</sub> | Maximum Clock Frequency                                           | 5.0                      | 120                                               | 140 |      |                                                                |     | 105                                                            |      | MHz   |          |
| t <sub>PLH</sub> | Propagation Delay, CP to Q <sub>n</sub><br>(PE Input HIGH or LOW) | 5.0                      | 1.5                                               | 5.5 | 10.0 |                                                                |     | 1.5                                                            | 11.0 | ns    | 2-3,4    |
| t <sub>PHL</sub> | Propagation Delay, CP to Q <sub>n</sub><br>(PE Input HIGH or LOW) | 5.0                      | 1.5                                               | 6.0 | 11.0 |                                                                |     | 1.5                                                            | 12.0 | ns    | 2-3,4    |
| t <sub>PLH</sub> | Propagation Delay<br>CP to TC                                     | 5.0                      | 2.5                                               | 7.0 | 11.5 |                                                                |     | 2.0                                                            | 13.5 | ns    | 2-3,4    |
| t <sub>PHL</sub> | Propagation Delay<br>CP to TC                                     | 5.0                      | 3.0                                               | 8.0 | 13.5 |                                                                |     | 2.0                                                            | 15.0 | ns    | 2-3,4    |
| t <sub>PLH</sub> | Propagation Delay<br>CET to TC                                    | 5.0                      | 2.0                                               | 5.5 | 9.0  |                                                                |     | 1.5                                                            | 10.5 | ns    | 2-3,4    |
| t <sub>PHL</sub> | Propagation Delay<br>CET to TC                                    | 5.0                      | 2.0                                               | 6.0 | 10.0 |                                                                |     | 2.0                                                            | 11.0 | ns    | 2-3,4    |

\*Voltage Range 5.0 is 5.0V ±0.5V

## AC Operating Requirements: See Section 2 for waveforms

| Symbol         | Parameter                                       | V <sub>CC</sub> *<br>(V) | 74ACT                                            |                    | 54ACT                                                         | 74ACT                                                        | Units | Fig. No. |
|----------------|-------------------------------------------------|--------------------------|--------------------------------------------------|--------------------|---------------------------------------------------------------|--------------------------------------------------------------|-------|----------|
|                |                                                 |                          | T <sub>A</sub> = +25°C<br>C <sub>L</sub> = 50 pF |                    | T <sub>A</sub> = -55°C<br>to +125°C<br>C <sub>L</sub> = 50 pF | T <sub>A</sub> = -40°C<br>to +85°C<br>C <sub>L</sub> = 50 pF |       |          |
|                |                                                 |                          | Typ                                              | Guaranteed Minimum |                                                               |                                                              |       |          |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>P <sub>n</sub> to CP | 5.0                      | 4.0                                              | 10.0               |                                                               | 12.0                                                         | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>P <sub>n</sub> to CP  | 5.0                      | -5.0                                             | 0.5                |                                                               | 0.5                                                          | ns    | 2-7      |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>SR to CP             | 5.0                      | 4.0                                              | 10.0               |                                                               | 11.5                                                         | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>SR to CP              | 5.0                      | -5.5                                             | -0.5               |                                                               | -0.5                                                         | ns    | 2-7      |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>PE to CP             | 5.0                      | 4.0                                              | 8.5                |                                                               | 10.5                                                         | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>PE to CP              | 5.0                      | -5.5                                             | -0.5               |                                                               | 0                                                            | ns    | 2-7      |
| t <sub>s</sub> | Setup Time, HIGH or LOW<br>CEP or CET to CP     | 5.0                      | 2.5                                              | 5.5                |                                                               | 6.5                                                          | ns    | 2-7      |
| t <sub>h</sub> | Hold Time, HIGH or LOW<br>CEP or CET to CP      | 5.0                      | -3.0                                             | 0                  |                                                               | 0.5                                                          | ns    | 2-7      |
| t <sub>w</sub> | Clock Pulse Width (Load)<br>HIGH or LOW         | 5.0                      | 2.0                                              | 3.5                |                                                               | 3.5                                                          | ns    | 2-3      |
| t <sub>w</sub> | Clock Pulse Width<br>(Count) HIGH or LOW        | 5.0                      | 2.0                                              | 3.5                |                                                               | 3.5                                                          | ns    | 2-3      |

\*Voltage Range 5.0 is 5.0V ±0.5V

## Capacitance

| Symbol   | Parameter                     | Typ  | Units | Conditions      |
|----------|-------------------------------|------|-------|-----------------|
| $C_{IN}$ | Input Capacitance             | 4.5  | pF    | $V_{CC} = 5.0V$ |
| $C_{PD}$ | Power Dissipation Capacitance | 45.0 | pF    | $V_{CC} = 5.0V$ |