



CY54/74FCT245T

8-Bit Transceiver

Features

- Function, pinout, and drive compatible with FCT, F logic
- FCT-C speed at 4.1 ns max. (Com'l)
FCT-A speed at 4.6 ns max. (Com'l)
- Reduced V_{DD} (typically = 3.3V) versions of equivalent FCT functions
- Edge-rate control circuitry for significantly improved noise characteristics
- Power-off disable feature
- ESD > 2000V

- Matched rise and fall times
- Fully compatible with TTL input and output logic levels
- Sink current 64 mA (Com'l),
48 mA (Mil)
Source current 32 mA (Com'l),
12 mA (Mil)

Functional Description


The FCT245T contains eight non-inverting bidirectional buffers with three-state outputs and is intended for bus oriented applications. For the

FCT245T, current sinking capability is 64 mA at the A and B ports.

The Transmit/Receiver (T/R) input determines the direction of data flow through bidirectional transceiver. Transmit (Active HIGH) enables data from A ports to B ports. The output enable (OE), when HIGH, disables both the A and B ports by putting them in a High Z condition.


The outputs are designed with a power-off disable feature to allow for live insertion of boards.

Logic Block Diagram




FCT245T-1

Pin Configurations



FCT245T-2



FCT245T-3

Function Table^[1]

OE	T/R	Operation
L	L	B Data to Bus A
L	H	A Data to Bus B
H	X	High Z State

Note:

1. H = HIGH Voltage Level, L = LOW Voltage Level, X = Don't Care.



Maximum Ratings^[2, 3]

(Above which the useful life may be impaired. For user guidelines, not tested.)

Storage Temperature	-65°C to +150°C
Ambient Temperature with Power Applied	-65°C to +135°C
Supply Voltage to Ground Potential	-0.5V to +7.0V
DC Input Voltage	-0.5V to +7.0V
DC Output Voltage	-0.5V to +7.0V
DC Output Current (Maximum Sink Current/Pin)	120 mA
Power Dissipation	0.5W

Static Discharge Voltage >2001V
(per MIL-STD-883, Method 3015)

Operating Range

Range	Range	Ambient Temperature	V _{CC}
Commercial	CT, DT	0°C to +70°C	5V ± 5%
Commercial	T, AT	-40°C to +85°C	5V ± 5%
Military ^[4]	All	-55°C to +125°C	5V ± 10%

Electrical Characteristics Over the Operating Range

Parameter	Description	Test Conditions	Min.	Typ. ^[5]	Max.	Unit
V _{OH}	Output HIGH Voltage	V _{CC} =Min., I _{OH} =-32 mA	2.0			V
		V _{CC} =Min., I _{OH} =-15 mA	2.4	3.3		V
		V _{CC} =Min., I _{OH} =-12 mA	2.4	3.3		V
V _{OL}	Output LOW Voltage	V _{CC} =Min., I _{OL} =64 mA		0.3	0.55	V
		V _{CC} =Min., I _{OL} =48mA		0.3	0.55	V
V _{IH}	Input HIGH Voltage		2.0			V
V _{IL}	Input LOW Voltage				0.8	V
V _{TI}	Hysteresis ^[6]	All inputs		0.2		V
V _{IK}	Input Clamp Diode Voltage	V _{CC} =Min., I _{IN} =-18 mA		-0.7	-1.2	V
I _I	Input HIGH Current	V _{CC} =Max., V _{IN} =V _{CC}			5	μA
I _{IH}	Input HIGH Current	V _{CC} =Max., V _{IN} =2.7V			±1	μA
I _{IL}	Input LOW Current	V _{CC} =Max., V _{IN} =0.5V			±1	μA
I _{OS}	Output Short Circuit Current ^[7]	V _{CC} =Max., V _{OUT} =0.0V	-60	-120	-225	mA
I _{OFF}	Power Off Disable	V _{CC} =0V, V _{OUT} =4.5V			±1	μA

Capacitance^[6]

Parameter	Description	Typ. ^[5]	Max.	Unit
C _{IN}	Input Capacitance	5	10	pF
C _{OUT}	Output Capacitance	9	12	pF

Notes:

- Unless otherwise noted, these limits are over the operating free air temperature range.
- Unused inputs must always be connected to an appropriate logic voltage level, preferably either V_{CC} or ground.
- T_A is the "instant on" case temperature.
- Typical values are at V_{CC}=5.0V, T_A=+25°C ambient.
- This parameter is guaranteed but not tested.
- Not more than one output should be shorted at a time. Duration of short should not exceed one second. The use of high-speed test apparatus and/or sample and hold techniques are preferable in order to minimize internal chip heating and more accurately reflect operational values. Otherwise prolonged shorting of a high output may raise the chip temperature well above normal and thereby cause invalid readings in other parametric tests. In any sequence of parameter tests, I_{OS} tests should be performed last.

Power Supply Characteristics

Parameter	Description	Test Conditions	Typ. ^[5]	Max.	Unit
I_{CC}	Quiescent Power Supply Current	$V_{CC} = \text{Max.}, V_{IN} \leq 0.2V,$ $V_{IN} \geq V_{CC} - 0.2V$	0.1	0.2	mA
AI_{CC}	Quiescent Power Supply Current (TTL inputs HIGH)	$V_{CC} = \text{Max.}, V_{IN} = 3.4V^{[8]}$ $t_I = 0, \text{Outputs Open}$	0.5	2.0	mA
I_{CCD}	Dynamic Power Supply Current ^[9]	$V_{CC} = \text{Max.}, \text{One Input Toggling},$ 50% Duty Cycle, Outputs Open, $T/R \text{ or } OE = GND \text{ and}$ $V_{IN} \leq 0.2V \text{ or } V_{IN} \geq V_{CC} - 0.2V$	0.06	0.12	mA/ MHz
I_C	Total Power Supply Current ^[10]	$V_{CC} = \text{Max.},$ 50% Duty Cycle, Outputs Open, One Bit Toggling at $f_I = 10 \text{ MHz},$ $T/R \text{ or } OE = GND \text{ and}$ $V_{IN} \leq 0.2V \text{ or } V_{IN} \geq V_{CC} - 0.2V$	0.7	1.4	mA
		$V_{CC} = \text{Max.},$ 50% Duty Cycle, Outputs Open, One Bit Toggling at $f_I = 10 \text{ MHz},$ $T/R \text{ or } OE = GND \text{ and}$ $V_{IN} = 3.4V \text{ or } V_{IN} = GND$	1.2	3.4	mA
		$V_{CC} = \text{Max.},$ 50% Duty Cycle, Outputs Open, Eight Bits Toggling at $f_I = 2.5 \text{ MHz},$ $T/R \text{ or } OE = GND \text{ and}$ $V_{IN} \leq 0.2V \text{ or } V_{IN} \geq V_{CC} - 0.2V$	1.3	2.6 ^[11]	mA
		$V_{CC} = \text{Max.},$ 50% Duty Cycle, Outputs Open, Eight Bits Toggling at $f_I = 2.5 \text{ MHz},$ $T/R \text{ or } OE = GND \text{ and}$ $V_{IN} = 3.4V \text{ or } V_{IN} = GND$	3.3	10.6 ^[11]	mA

Notes:

8. Per TTL driven input ($V_{IN} = 3.4V$); all other inputs at V_{CC} or GND.

9. This parameter is not directly testable, but is derived for use in Total Power Supply calculations.

10. $I_C = I_{CC} + AI_{CC} + I_{CCD}$

$I_C = I_{CC} + AI_{CC} D_H N_T + I_{CCD} (f_0/2 + f_I N_I)$

$I_{CC} = \text{Quiescent Current with CMOS input levels}$

$AI_{CC} = \text{Power Supply Current for a TTL HIGH input}$
($V_{IN} = 3.4V$)

$D_H = \text{Duty Cycle for TTL inputs HIGH}$

$N_T = \text{Number of TTL inputs at } D_H$

$I_{CCD} = \text{Dynamic Current caused by an input transition pair}$
(HLH or LHL.)

$f_0 = \text{Clock frequency for registered devices, otherwise zero}$

$f_I = \text{Input signal frequency}$

$N_I = \text{Number of inputs changing at } f_I$

All currents are in milliamps and all frequencies are in megahertz.

11. Values for these conditions are examples of the I_{CC} formula. These limits are guaranteed but not tested.

Switching Characteristics Over the Operating Range

Parameter	Description	FCT245T				FCT245AT				Unit	Fig. No. ^[13]
		Military		Commercial		Military		Commercial			
		Min. ^[12]	Max.	Min. ^[12]	Max.	Min. ^[12]	Max.	Min. ^[12]	Max.		
t _{PLH} t _{PHL}	Propagation Delay A to B or B to A	1.5	7.5	1.5	7.0	1.5	4.9	1.5	4.6	ns	1, 3
t _{PZH} t _{PZL}	Output Enable Time OE or T/R to A or B	1.5	10.0	1.5	9.5	1.5	6.5	1.5	6.2	ns	1, 7, 8
t _{PLZ} t _{PLZ}	Output Disable Time OE or T/R to A or B	1.5	10.0	1.5	7.5	1.5	6.0	1.5	5.0	ns	1, 7, 8

Switching Characteristics Over the Operating Range

Parameter	Description	FCT245CT				FCT245DT		Unit	Fig. No. [13]
		Military		Commercial		Commercial			
		Min. [12]	Max.	Min. [12]	Max.	Min. [12]	Max.		
t _{PLH} t _{PHL}	Propagation Delay A to B or B to A	1.5	4.5	1.5	4.1	1.5	3.8	ns	1, 3
t _{PZH} t _{PZL}	Output Enable Time OE or T/R to A or B	1.5	6.2	1.5	5.8	1.5	5.0	ns	1, 7, 8
t _{PLZ} t _{PLZ}	Output Disable Time OE or T/R to A or B	1.5	5.2	1.5	4.8	1.5	4.3	ns	1, 7, 8

Shaded areas contain preliminary information.

Notes:

12. Minimum limits are guaranteed but not tested on Propagation Delays.
13. See "Parameter Measurement Information" in the General Information Section.



Ordering Information

Speed (ns)	Ordering Code	Package Name	Package Type	Operating Range
3.8	CY74FCT245DTQC	Q5	20-Lead (150-Mil) QSOP	Commercial
	CY74FCT245DTSOC	S5	20-Lead (300-Mil) Molded SOIC	
4.1	CY74FCT245CTPC	P5	20-Lead (300-Mil) Molded DIP	Commercial
	CY74FCT245CTQC	Q5	20-Lead (150-Mil) QSOP	
	CY74FCT245CTSOC	S5	20-Lead (300-Mil) Molded SOIC	
4.5	CY54FCT245CTDMB	D6	20-Lead (300-Mil) CerDIP	Military
	CY54FCT245CTLMB	L61	20-Square Leadless Chip Carrier	
4.6	CY74FCT245ATPC	P5	20-Lead (300-Mil) Molded DIP	Commercial
	CY74FCT245ATQC	Q5	20-Lead (150-Mil) QSOP	
	CY74FCT245ATSOC	S5	20-Lead (300-Mil) Molded SOIC	
4.9	CY54FCT245ATDMB	D6	20-Lead (300-Mil) CerDIP	Military
	CY54FCT245ATLMB	L61	20-Square Leadless Chip Carrier	
7.0	CY74FCT245TPC	P5	20-Lead (300-Mil) Molded DIP	Commercial
	CY74FCT245TQC	Q5	20-Lead (150-Mil) QSOP	
	CY74FCT245TSOC	S5	20-Lead (300-Mil) Molded SOIC	
7.5	CY54FCT245TDMB	D6	20-Lead (300-Mil) CerDIP	Military
	CY54FCT245TLMB	L61	20-Square Leadless Chip Carrier	

Shaded areas contain preliminary information.

Document #: 38-00318-A