



CD4042BM/CD4042BC Quad Clocked D Latch


General Description

The CD4042BM/CD4042BC quad clocked "D" latch is a monolithic complementary MOS (CMOS) integrated circuit constructed with P- and N-channel enhancement mode transistors. The outputs Q and $\bar{Q}$ either latch or follow the data input depending on the clock level which is programmed by the polarity input. For polarity = 0; the information present at the data input is transferred to Q and $\bar{Q}$ during 0 clock level; and for polarity = 1, the transfer occurs during the 1 clock level. When a clock transition occurs (positive for polarity = 0 and negative for polarity = 1), the information present at the input during the clock transition is retained at the outputs until an opposite clock transition occurs.

Features

- Wide supply voltage range 3.0V to 15V
- High noise immunity 0.45 V_{DD} (typ.)
- Low power TTL compatibility fan out of 2 driving 74L or 1 driving 74LS
- Clock polarity control
- Fully buffered data inputs
- Q and $\bar{Q}$ outputs


Connection Diagram



Truth Table

CLOCK	POLARITY	Q
0	0	D
	0	Latch
1	1	D
	1	Latch

Logic Diagrams



Absolute Maximum Ratings

(Notes 1 and 2)

V _{DD} Supply Voltage	-0.5V to +18V
V _{IN} Input Voltage	-0.5V to V _{DD} + 0.5V
T _S Storage Temperature Range	-65°C to +150°C
P _D Package Dissipation	500 mW
T _L Lead Temperature (Soldering, 10 seconds)	300°C

Recommended Operating Conditions

(Note 2)

V _{DD} Supply Voltage	3V to 15V
V _{IN} Input Voltage	0V to V _{DD}
T _A Operating Temperature Range	-55°C to +125°C
CD4042BM	-40°C to +85°C
CD4042BC	

DC Electrical Characteristics CD4042BM (Note 2)

PARAMETERS	CONDITIONS	-55°C		25°C			125°C		UNITS
		MIN	MAX	MIN	TYP	MAX	MIN	MAX	
I _{DD} Quiescent Device Current	V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V		1 2 4		0.02 0.02 0.02	1 2 4		30 60 120	μA
V _{OL} Low Level Output Voltage	I _O < 1 μA, V _{IH} = V _{DD} , V _{IL} = 0V V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V		0.05 0.05 0.05		0 0 0	0.05 0.05 0.05		0.05 0.05 0.05	V
V _{OH} High Level Output Voltage	I _O < 1 μA, V _{IH} = V _{DD} , V _{IL} = 0V V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V	4.95 9.95 14.95		4.95 9.95 14.95	5 10 15		4.95 9.95 14.95		V
V _{IL} Low Level Input Voltage	I _O < 1 μA V _{DD} = 5V, V _O = 0.5V or 4.5V V _{DD} = 10V, V _O = 1V or 9V V _{DD} = 15V, V _O = 1.5V or 13.5V		1.5 3.0 4.0		2.25 4.5 6.75	1.5 3.0 4.0		1.5 3.0 4.0	V
V _{IH} High Level Input Voltage	I _O < 1 μA V _{DD} = 5V, V _O = 0.5V or 4.5V V _{DD} = 10V, V _O = 1V or 9V V _{DD} = 15V, V _O = 1.5V or 13.5V	3.5 7.0 11.0		3.5 7.0 11.0	2.75 5.5 8.25		3.5 7.0 11.0		V
I _{OL} Low Level Output Current	V _{IH} = V _{DD} , V _{IL} = 0V V _{DD} = 5V, V _O = 0.4V V _{DD} = 10V, V _O = 0.5V V _{DD} = 15V, V _O = 1.5V	0.64 1.6 4.2		0.51 1.3 3.4	0.88 2.25 8.8		0.36 0.9 2.4		mA
I _{OH} High Level Output Current	V _{IH} = V _{DD} , V _{IL} = 0V V _{DD} = 5V, V _O = 4.6V V _{DD} = 10V, V _O = 9.5V V _{DD} = 15V, V _O = 13.5V	-0.64 -1.6 -4.2		-0.51 -1.3 -3.4	-0.88 -2.25 -8.8		-0.36 -0.9 -2.4		mA
I _{IN} Input Current	V _{DD} = 15V, V _{IN} = 0V V _{DD} = 15V, V _{IN} = 15V		-0.1 0.1		-10 ⁻⁵ 10 ⁻⁵	-0.1 0.1		-1.0 1.0	μA

DC Electrical Characteristics CD4042BC (Note 2)

PARAMETER	CONDITIONS	-40°C		25°C			85°C		UNITS
		MIN	MAX	MIN	TYP	MAX	MIN	MAX	
I _{DD} Quiescent Device Current	V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V		4 8 16		0.02 0.02 0.02	4 8 16		30 60 120	μA
V _{OL} Low Level Output Voltage	I _O < 1 μA, V _{IH} = V _{DD} , V _{IL} = 0V V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V		0.05 0.05 0.05		0 0 0	0.05 0.05 0.05		0.05 0.05 0.05	V
V _{OH} High Level Output Voltage	I _O < 1 μA, V _{IH} = V _{DD} , V _{IL} = 0V V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V	4.95 9.95 14.95		4.95 9.95 14.95	5 10 15		4.95 9.95 14.95		V
V _{IL} Low Level Input Voltage	I _O < 1 μA V _{DD} = 5V, V _O = 0.5V or 4.5V V _{DD} = 10V, V _O = 1V or 9V V _{DD} = 15V, V _O = 1.5V or 13.5V		1.5 3.0 4.0		2.25 4.5 6.75	1.5 3.0 4.0		1.5 3.0 4.0	V

DC Electrical Characteristics (Cont'd.) CD4042BC (Note 2)

PARAMETER	CONDITIONS	-40°C		25°C			85°C		UNITS
		MIN	MAX	MIN	TYP	MAX	MIN	MAX	
V_{IH} High Level Input Voltage	$ I_{OI} < 1 \mu A$								
	$V_{DD} = 5V, V_O = 0.5V \text{ or } 4.5V$	3.5		3.5	2.75		3.5		V
	$V_{DD} = 10V, V_O = 1V \text{ or } 9V$	7.0		7.0	5.5		7.0		V
	$V_{DD} = 15V, V_O = 1.5V \text{ or } 13.5V$	11.0		11.0	8.25		11.0		V
I_{OL} Low Level Output Current	$V_{IH} = V_{DD}, V_{IL} = 0V$								
	$V_{DD} = 5V, V_O = 0.4V$	0.52		0.44	0.88		0.36		mA
	$V_{DD} = 10V, V_O = 0.5V$	1.3		1.1	2.25		0.9		mA
	$V_{DD} = 15V, V_O = 1.5V$	3.6		3.0	8.8		2.4		mA
I_{OH} High Level Output Current	$V_{IH} = V_{DD}, V_{IL} = 0V$								
	$V_{DD} = 5V, V_O = 4.6V$	-0.52		-0.44	-0.88		-0.36		mA
	$V_{DD} = 10V, V_O = 9.5V$	-1.3		-1.1	-2.25		-0.9		mA
	$V_{DD} = 15V, V_O = 13.5V$	-3.6		-3.0	-8.8		-2.4		mA
I_{IN} Input Current	$V_{DD} = 15V, V_{IN} = 0V$		-0.3		-10^{-5}	-0.3		-1.0	μA
	$V_{DD} = 15V, V_{IN} = 15V$		0.3		10^{-5}	0.3		1.0	μA

AC Electrical Characteristics $T_A = 25^\circ C$, $C_L = 50 pF$, $R_L = 200 k$, Input $t_r = t_f = 20 ns$, unless otherwise specified

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
t_{PHL}, t_{PLH} Propagation Delay Time Data In to Q	$V_{DD} = 5V$		175	350	ns
	$V_{DD} = 10V$		75	150	ns
	$V_{DD} = 15V$		60	120	ns
t_{PHL}, t_{PLH} Propagation Delay Time Data In to $\bar{Q}$	$V_{DD} = 5V$		150	300	ns
	$V_{DD} = 10V$		75	150	ns
	$V_{DD} = 15V$		50	100	ns
t_{PHL}, t_{PLH} Propagation Delay Time Clock to Q	$V_{DD} = 5V$		250	500	ns
	$V_{DD} = 10V$		100	200	ns
	$V_{DD} = 15V$		80	160	ns
t_{PHL}, t_{PLH} Propagation Delay Time Clock to $\bar{Q}$	$V_{DD} = 5V$		250	500	ns
	$V_{DD} = 10V$		115	230	ns
	$V_{DD} = 15V$		90	180	ns
t_H Minimum Hold Time	$V_{DD} = 5V$		60	120	ns
	$V_{DD} = 10V$		30	60	ns
	$V_{DD} = 15V$		25	50	ns
t_{SU} Minimum Set-Up Time	$V_{DD} = 5V$		0	50	ns
	$V_{DD} = 10V$		0	30	ns
	$V_{DD} = 15V$		0	25	ns
t_W Minimum Clock Pulse Width	$V_{DD} = 5V$		100	200	ns
	$V_{DD} = 10V$		50	100	ns
	$V_{DD} = 15V$		30	60	ns
t_{THL}, t_{TLH} Transition Time	$V_{DD} = 5V$		125	250	ns
	$V_{DD} = 10V$		60	125	ns
	$V_{DD} = 15V$		50	100	ns
C_{IN} Input Capacitance	Any Input		5.0	7.5	pF

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the devices should be operated at these limits. The tables of "Recommended Operating Conditions" and "Electrical Characteristics" provide conditions for actual device operation.

Note 2: $V_{SS} = 0V$ unless otherwise specified.

Note 3: Being a latch, the CD4042BM/CD4042BC is not clock rise and fall time sensitive.

Switching Time Waveforms

