



CD4512M/CD4512C 8-Channel Data Selector

General Description


The CD4512M/CD4512C 8-channel data selector is a complementary MOS (CMOS) circuit constructed with N- and P-channel enhancement mode transistors. This data selector is primarily used as a digital signal multiplexer selecting 1 of 8 inputs and routing the signal to a TRI-STATE® output. A high level at the Inhibit input forces a low level at the output. A high level at the Output Enable ($\overline{OE}$) input forces the output into the TRI-STATE condition. Low levels at both the Inhibit and ($\overline{OE}$) inputs allow normal operation.

TRI-STATE is a trademark of National Semiconductor Corp.

Features

- Wide supply voltage range 3.0V-15V
- High noise immunity 0.45 V_{DD} (typ.)
- TRI-STATE output
- Low quiescent power dissipation 0.25 μW /package (typ.) @ $V_{CC} = 5.0V$
- Plug-in replacement for Motorola MC14512

Connection Diagram and Truth Table



ADDRESS INPUTS			CONTROL INPUTS		OUTPUT
C	B	A	INHIBIT	$\overline{OE}$	Z
0	0	0	0	0	X0
0	0	1	0	0	X1
0	1	0	0	0	X2
0	1	1	0	0	X3
1	0	0	0	0	X4
1	0	1	0	0	X5
1	1	0	0	0	X6
1	1	1	0	0	X7
0	0	0	1	0	0
0	0	0	0	1	Hi-Z

0 = Don't care

Hi-Z = TRI-STATE® condition

Xn = Data at input n

Absolute Maximum Ratings

(Notes 1 & 2)

V_{DD} Supply Voltage	-0.5 to +18 V_{DC}
V_{IN} Input Voltage	-0.5 to $V_{DD} + 0.5 V_{DC}$
T_S Storage Temperature Range	-65°C to +150°C
P_D Package Dissipation	500 mW
T_L Lead Temperature (Soldering, 10 seconds)	300°C

Recommended Operating Conditions

(Note 2)

V_{DD} DC Supply Voltage	3.0 to 15 V_{DC}
V_{IN} Input Voltage	0 to $V_{DD} V_{DC}$
T_A Operating Temperature Range	-55°C to +125°C
CD4512M	-55°C to +125°C
CD4512C	-40°C to +85°C

DC Electrical Characteristics CD4512M (Note 2)

Parameter	Conditions	-55°C		25°C			125°C		Units
		Min.	Max.	Min.	Typ.	Max.	Min.	Max.	
I_{DD} Quiescent Device Current	$V_{DD} = 5.0 V$		5.0		0.005	5.0		150	μA
	$V_{DD} = 10 V$		10		0.010	10		300	μA
	$V_{DD} = 15 V$		20		0.015	20		600	μA
V_{OL} Low Level Output Voltage	$V_{DD} = 5.0 V$		0.05		0	0.05		0.05	V
	$V_{DD} = 10 V$		0.05		0	0.05		0.05	V
	$V_{DD} = 15 V$		0.05		0	0.05		0.05	V
V_{OH} High Level Output Voltage	$V_{DD} = 5.0 V$	4.95		4.95	5.0		4.95		V
	$V_{DD} = 10 V$	9.95		9.95	10.0		9.95		V
	$V_{DD} = 15 V$	14.95		14.95	15.0		14.95		V
V_{IL} Low Level Input Voltage	$V_{DD} = 5.0 V, V_O = 0.5 V$		1.5		2.25	1.5		1.5	V
	$V_{DD} = 10 V, V_O = 1.0 V$		3.0		4.50	3.0		3.0	V
	$V_{DD} = 15 V, V_O = 1.5 V$		4.0		6.75	4.0		4.0	V
V_{IH} High Level Input Voltage	$V_{DD} = 5.0 V, V_O = 4.5 V$	3.5		3.5	2.75		3.5		V
	$V_{DD} = 10 V, V_O = 9.0 V$	7.0		7.0	5.50		7.0		V
	$V_{DD} = 15 V, V_O = 13.5 V$	11.0		11.0	8.25		11.0		V
I_{OL} Low Level Output Current	$V_{DD} = 5.0 V, V_O = 0.4 V$	0.50		0.40	0.78		0.38		mA
	$V_{DD} = 10 V, V_O = 0.5 V$	1.1		0.90	2.0		0.9		mA
	$V_{DD} = 15 V, V_O = 1.5 V$	4.2		3.4	7.8		2.4		mA
I_{OH} High Level Output Current	$V_{DD} = 5.0 V, V_O = 4.6 V$	-0.62		-0.50	-1.7		-0.35		mA
	$V_{DD} = 10 V, V_O = 9.5 V$	-0.62		-0.50	-1.9		-0.35		mA
	$V_{DD} = 15 V, V_O = 13.5 V$	-1.8		-1.5	-3.5		-1.1		mA
I_{IN} Input Current	$V_{DD} = 15 V, V_{IN} = 0 V$		-0.1		-10^{-5}	-0.1		-1.0	μA
	$V_{DD} = 15 V, V_{IN} = 15 V$		0.1		10^{-}	0.1		1.0	μA
I_{OZ} TRI-STATE® Output Current	$V_{DD} = 15 V, V_O = 0 V$		± 0.1		-10^{-5}	± 0.1		± 3.0	μA
	$V_{DD} = 15 V, V_O = 15 V$				10^{-5}				μA

DC Electrical Characteristics CD4512C (Note 2)

Parameter	Conditions	-40°C		25°C			85°C		Units
		Min.	Max.	Min.	Typ.	Max.	Min.	Max.	
I_{DD} Quiescent Device Current	$V_{DD} = 5.0 V$		20		0.005	20		150	μA
	$V_{DD} = 10 V$		40		0.010	40		300	μA
	$V_{DD} = 15 V$		80		0.015	80		600	μA
V_{OL} Low Level Output Voltage	$V_{DD} = 5.0 V$		0.05		0	0.05		0.05	V
	$V_{DD} = 10 V$		0.05		0	0.05		0.05	V
	$V_{DD} = 15 V$		0.05		0	0.05		0.05	V
V_{OH} High Level Output Voltage	$V_{DD} = 5.0 V$	4.95		4.95	5.0		4.95		V
	$V_{DD} = 10 V$	9.95		9.95	10.0		9.95		V
	$V_{DD} = 15 V$	14.95		14.95	15.0		14.95		V
V_{IL} Low Level Input Voltage	$V_{DD} = 5.0 V, V_O = 0.5 V$		1.5		2.25	1.5		1.5	V
	$V_{DD} = 10 V, V_O = 1.0 V$ or $9.0 V$		3.0		4.50	3.0		3.0	V
	$V_{DD} = 15 V, V_O = 1.5 V$ or $13.5 V$		4.0		6.75	4.0		4.0	V
V_{IH} High Level Input Voltage	$V_{DD} = 5.0 V, V_O = 4.5 V$	3.5		3.5	2.75		3.5		V
	$V_{DD} = 10 V, V_O = 9.0 V$	7.0		7.0	5.50		7.0		V
	$V_{DD} = 15 V, V_O = 1.5 V$ or $13.5 V$	11.0		11.0	8.25		11.0		V

DC Electrical Characteristics (cont'd) CD4512C (Note 2)

Parameter	Conditions	-40°C		25°C			85°C		Units
		Min.	Max.	Min.	Typ.	Max.	Min.	Max.	
I_{OL} Low Level Output Current	$V_{DD} = 5.0\text{ V}, V_O = 0.4\text{ V}$	0.23		0.20	0.78		0.16		mA
	$V_{DD} = 10\text{ V}, V_O = 0.5\text{ V}$	0.60		0.50	2.0		0.09		mA
	$V_{DD} = 15\text{ V}, V_O = 1.5\text{ V}$	1.8		1.5	7.8		1.2		mA
I_{OH} High Level Output Current	$V_{DD} = 5.0\text{ V}, V_O = 2.5\text{ V}$	-0.23		-0.20	-1.7		-0.16		mA
	$V_{DD} = 10\text{ V}, V_O = 9.5\text{ V}$	-0.23		-0.20	-0.9		-0.16		mA
	$V_{DD} = 15\text{ V}, V_O = 113.5\text{ V}$	-0.69		-0.60	-3.5		-0.48		mA
I_{IN} Input Current	$V_{DD} = 15\text{ V}, V_{IN} = 0\text{ V}$		-0.3		-10^{-5}	-0.3		-1.0	μA
	$V_{DD} = 15\text{ V}, V_{IN} = 15\text{ V}$		0.3		10^{-5}	0.3		1.0	μA
I_{OZ} TRI-STATE [®] Output Current	$V_{DD} = 15\text{ V}, V_O = 0\text{ V or } 15\text{ V}$		± 1.0		$\pm 10^{-5}$	± 1.0		± 7.5	μA

AC Electrical Characteristics $T_A = 25^\circ\text{C}, t_r = t_f = 20\text{ ns}, C_L = 15\text{ pF}$

Parameter	Conditions	CD4512M			CD4512C			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
t_{PHL} Propagation Delay High-to-Low Level	$V_{DD} = 5.0\text{ V}$		225	500		225	750	ns
	$V_{DD} = 10\text{ V}$		75	175		75	200	ns
	$V_{DD} = 15\text{ V}$		57	130		57	150	ns
t_{PLH} Propagation Delay Low-to-High Level	$V_{DD} = 5.0\text{ V}$		225	500		225	750	ns
	$V_{DD} = 10\text{ V}$		75	175		75	200	ns
	$V_{DD} = 15\text{ V}$		57	130		57	150	ns
t_{THL}, t_{TLH} Transition Time	$V_{DD} = 5.0\text{ V}$		70	175		70	175	ns
	$V_{DD} = 10\text{ V}$		35	75		35	75	ns
	$V_{DD} = 15\text{ V}$		25	55		25	55	ns
t_{PHZ}, t_{PLZ} Propagation Delay into TRI-STATE from Logic Level	$V_{DD} = 5.0\text{ V}$		50	125		50	125	ns
	$V_{DD} = 10\text{ V}$		25	75		25	75	ns
	$V_{DD} = 15\text{ V}$		19	60		19	60	ns
t_{PZH}, t_{PZL} Propagation Delay to Logic Level from TRI-STATE	$V_{DD} = 5.0\text{ V}$		50	125		50	125	ns
	$V_{DD} = 10\text{ V}$		25	75		25	75	ns
	$V_{DD} = 15\text{ V}$		19	60		19	60	ns
C_{IN} Input Capacitance	(Note 3)		7.5	15		7.5	15	pF
C_{OUT} TRI-STATE Output Capacitance	(Note 3)		7.5	15		7.5	15	pF
C_{PD} Power Dissipation Capacity	(Note 4)		150			150		pF


Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the devices should be operated at these limits. The tables of "Recommended Operating Conditions" and "Electrical Characteristics" provide conditions for actual device operation.

Note 2: $V_{SS} = 0\text{ V}$ unless otherwise specified.

Note 3: Capacitance guaranteed by periodic testing.


Note 4: C_{PD} determines the no load AC power of any CMOS device. For complete explanation, see 54C/74C Family Characteristics application note AN-90.

Logic Diagram





Typical Application

Serial Data Routing Interface





AC Test Circuit and Switching Time Waveforms



INPUT CONNECTIONS FOR t_r , t_f , t_{PLH} , t_{PHL}

TEST	INHIBIT	A	X0
1	PG	GND	VDD
2	GND	PG	VDD
3	GND	GND	PG

TRI-STATE AC Test Circuit and Switching Time Waveforms



SWITCH POSITIONS FOR TRI-STATE TEST

TEST	S1	S2	S3	S4
t_{PHZ}	Open	Closed	Closed	Open
t_{PLZ}	Closed	Open	Open	Closed
t_{PZL}	Closed	Open	Open	Closed
t_{PZH}	Open	Closed	Closed	Open