

NE544 Servo Amplifier

Product Specification

Linear Products

DESCRIPTION

The NE544 is a servo amplifier and pulse-width demodulator with internal motor drive transistors. It is designed for remote control applications in digital proportional systems but can be used in many other closed-loop position control applications. It incorporates a linear one-shot for improved positional accuracy and outputs for external PNP motor drive transistors.

FEATURES

- 500mA load current capability
- Bidirectional bridge output with single power supply
- Low standby power drain
- Adjustable deadband and trigger thresholds
- High linearity, 0.5% maximum error
- Output drive for external PNP transistors (optional)
- Wide supply voltage range

APPLICATIONS

- Miniature position servo
- Robotics
- Control devices
- Remote positioning


ORDERING INFORMATION

DESCRIPTION	TEMPERATURE RANGE	ORDER CODE
14-Pin Plastic DIP	0 to +70°C	NE544N
16-Pin Plastic SOL Package	0 to +70°C	NE544D

ABSOLUTE MAXIMUM RATINGS $T_A = 25^\circ\text{C}$ unless otherwise specified.

SYMBOL	PARAMETER	RATING	UNIT
V_+	Supply voltage	6.0	V
I_O	Output current D package N package	400 500	mA
T_A	Operating temperature	0 to +70	°C
T_{STG}	Storage temperature	-65 to +150	°C


PIN CONFIGURATIONS



Servo Amplifier

NE544


BLOCK DIAGRAM



Servo Amplifier

NE544

EQUIVALENT SCHEMATIC




Servo Amplifier

NE544

DC ELECTRICAL CHARACTERISTICS $T_A = 25^{\circ}\text{C}$, $V_S = 4.8\text{V}$ unless otherwise specified.

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
V_{CC}	Supply voltage	Quiescent	3.2	4.8	6	V
I_{CC}	Supply current, Pin 11		4.2	5.5	10	mA
V_{TH}	Input threshold, Pin 4			1.5		V
	On Off			1.4		
Z_{IN}	Input resistance, Pin 4			18		$k\Omega$
V_{OL} V_{OH}	Output voltage Low High	Pin 9 or 13. $I_L = 400\text{mA}$		0.3 3.9		V
V_{REG}	Regulated voltage, Pin 3		2.1	2.5	2.9	V
ΔV_{REG}	Regulation, Pin 3 Minimum deadband, Pin 7 One-shot temperature coefficient	$3.9\text{V} \leq V_{CC} \leq 6\text{V}$ $R_{DB} = 0$		10 1 0.01		mV/V μs %/°C
	Standby output voltage PNP drive current	Pins 9 and 13 Pins 10 and 12		2.5 20		V mA


TYPICAL CONNECTION OF NE544N FOR LINEAR ONE-SHOT TIMING



Servo Amplifier

NE544


PC BOARD — N PACKAGE




Servo Amplifier

NE544


TYPICAL PERFORMANCE CHARACTERISTICS

Maximum Dissipation vs
Ambient Temperature


OP194815

Supply Current vs
Supply Voltage


OP194905

Output Current vs
Load Resistance


OP195018

Output Voltage vs
Load Current

OP195105

Input Pulse Width vs
Feedback Pot Output

OP195205

Input Pulse vs
Servo Travel

OP195305